

IBM DDS Generation 5 USB Tape Drive (Withdrawn)

Product Guide (withdrawn product)

The IBM DDS Generation 5 USB tape drive is the entry point into the IBM DDS tape drive family and offers dependable capacity and performance for value-conscious small and medium or distributed large enterprise businesses. DDS/DAT technology has the proven reliability and low cost of ownership to effectively meet the demanding backup, archival, and regulatory compliance requirements of your System x environment.

IBM DDS Generation 5 technology delivers a capacity of up to 72 GB on a single data cartridge and a transfer rate of up to 22 GB/hr (assuming a 2:1 compression ratio) at an entry price point. Its USB 2.0 interface supports internal plug and play capability with the latest System x systems, as well as external attachment in one of IBM's external tape drive enclosures. DDS Generation 5 technology is also backward read and write compatible with DDS-3 and DDS-4/DAT 40 media to ensure an easy migration or upgrade path for existing DDS/DAT users.

Figure 1 shows the DDS Generation 5 USB Tape Drive in its 5.25 inch form factor.



Figure 1. The DDS Generation 5 USB Tape Drive

Did you know?

DDS/DAT products are built on a legacy of reliability and investment over many years. Reliability features include proven media, careful tape handling, two write heads for read-while-writing data verification, and advanced levels of error correction. DDS/DAT media is specified with a dependable shelf life in excess of 15 years, ideal for meeting today's business and regulatory long-term archival requirements.

Part number information

Table 1 lists the ordering part numbers and feature codes.

Table 1. Ordering part numbers and feature codes

Description	Part number	Feature code
IBM DDS Generation 5 USB Tape Drive	46C5399	5711
IBM DDS Generation 5 Media 5-Pack Option	71P9158	Not available
IBM DDS Generation 5 Single Cartridge Option	59H4456	Not available
IBM DDS Generation 5 Cleaning Cartridge	49Y9892*	Not available

* Planned for May 2011

The part number for the DDS Generation 5 USB Tape Drive includes the following items:

- IBM DDS Generation 5 USB Tape Drive (5.25 inch form factor)
- Mounting screws
- CD-ROM containing the *DDS Generation 5 USB Tape Drive User's Guide*
- Cleaning cartridge
- Four USB cables for internal tape connectivity:
 - 14 inch USB cable with type 2x3 connector x3200 and x3200 M2
 - 28 inch USB cable with type B connector for x3400 and x3500
 - 12.5 inch USB cable with type 1x6 connector x3650 and x3655
 - 40 inch USB cable with type A locking connector for all other supported systems

The drive can be converted to a 3.5 inch form factor for use in some rack-optimized servers, which we describe later in the section "Internal installation."

Features

The DDS Generation 5 USB Tape Drive provides convenience and ease-of-use features while supporting high speed tape backup. The DDS Generation 5 USB Tape Drive provides the following features and capabilities:

- USB interface allows for direct internal connections with select System x servers
- Eliminates potential RAID conflicts and extra controllers
- 5.25 inch half-high form factor
- Drive can be converted to 3.5 inch form factor either in the factory (CTO) or in the field using the appropriate enablement kit
- Internal USB interface for simplified plug-and-play installation
- Optional DDS Tape Enablement kits allow for internal installation in select IBM System x rack-optimized servers
- Flexible external USB configuration offerings when used with desktop or 1U rack-mount enclosures
- Support for leading operating systems and popular backup software

Specifications

The DDS Generation 5 USB Tape Drive has the following specifications:

- Up to 36 GB native capacity, and up to 72 GB in compressed mode
- Up to 3.0 MBps native back-up rate, and up to 6.0 MBps in compressed mode
- USB 2.0 interface
- Read/write compatibility with DDS-4, and DDS-3 cartridges

Prerequisites

- Available internal or external USB port
- Available 5.25 inch half-high bay for internal installations
- Supported external tape enclosure for external attachment

Physical specifications

The DDS Generation 5 USB Tape Drive has the following physical specifications:

- Height: 41 mm (1.6 in)
- Width: 102 mm (4 in)
- Depth: 150 mm (5.9 in)
- Weight: 0.72 kg (1.6 lb)

Operating environment

The DDS Generation 5 USB Tape Drive is supported in the following environment:

- Temperature:
 - Operating: 5° to 40°C (41° to 104°F)
 - Non-operating: -40° to 70°C (-40° to 158°F)
- Relative humidity:
 - Operating: 20% to 80% (non-condensing)
 - Non-operating: 5% to 90% (non-condensing)
- Maximum altitude:
 - Operating: 0 m to 4600 m (0 to 15000 ft.)
 - Non-operating: 0 m to 15200 m (0 to 50000 ft.)

Warranty

The DDS Generation 5 USB Tape Drive has a one-year limited warranty on parts only. When installed in a System x server, this tape drive assumes your system's base warranty or external enclosure, and any IBM ServicePac upgrade.

The IBM DDS Generation 5 Media 5 Pack has a limited lifetime warranty.

Supported servers

The DDS Generation 5 USB Tape Drive is supported in the IBM System x servers listed in Table 2.

Table 2. Supported System x servers (Part 1)

	x3100 M3	x3200 M2	x3200 M3	x3250 M2	x3250 M3	x3350	x3400	x3400 M2	x3400 M3	x3455	x3500	x3500 M2	x3500 M3
DDS Generation 5 USB Tape Drive (external)	N	Y	Y	Y	Y	N	Y	Y	Y	N	Y	Y	Y
DDS Generation 5 USB Tape Drive (internal)	N	Y	Y	N	N	N	Y	Y	Y	N	Y	Y	Y

Table 2. Supported System x servers (Part 2)

	x3550	x3550 M2	x3550 M3	x3620 M3	x3630 M3	x3650	x3650 T	x3650 M2	x3650 M3	x3655	x3690 X5	x3755	x3755 M3	x3850 M2	x3950 M2	x3850 X5
DDS Generation 5 USB Tape Drive (external)	N	Y	N	Y	Y	Y	N	Y	Y	Y	N	N	Y	N	N	N
DDS Generation 5 USB Tape Drive (internal)	N	N	N	Y†	N	Y†	N	Y†	Y†	Y†	N	N	Y†	N	N	N

† To use the tape drive internally in these servers, the drive is converted to a 3.5-inch form factor, as described in the next section

See IBM ServerProven for the latest information about the devices supported by each System x server type:
<http://ibm.com/servers/eserver/serverproven/compat/us/>

Internal installation

The DDS Generation 5 USB Tape Drive can be installed internally in specific servers as listed in Table 2. Except where noted, the DDS Generation 5 USB Tape Drive is installed in its standard 5.25-inch form factor.

As listed with a † symbol in Table 2, various servers support the tape drive mounted internally with the addition of a 3.5-inch tape enablement kit. The specific tape enablement kits that are supported are listed in Table 3.

Table 3. The 3.5-inch enablement kits for use with the DDS Generation 5 USB Tape Drive

			x3620 M3	x3650	x3650 M2	x3650 M3	x3655	x3755 M3
IBM DDS Tape Enablement Kit	43V5959	5387 / 4873‡	N	Y	N	N	Y*	N
IBM System x3650 M2 RDX-DDS Tape Enablement Kit	49Y9883	7551	N	N	Y	N	N	N
Tape Enablement Kit option for x3650 M3	59Y3806	1746	N	N	N	Y	N	N
IBM x3620 M3 Tape Enablement Kit	69Y0798	6419	Y	N	N	N	N	N
Tape Enablement Kit for x3755 M3	69Y1456	4787	N	N	N	N	N	Y†

* The installation of IBM DDS Tape Enablement Kit in an x3655 is in the field only. Installation is not available as a factory installation (CTO) option.

‡ Feature 4873 is for 2.5 inch disk drive models of the x3650, 5387 is for 3.5 inch disk drive models of the x3650

† The tape drive enablement kit for the x3755 M3 is only supported in systems with a simple-swap backplane and drives

See IBM ServerProven for the latest information about the devices supported by each System x server type:

<http://ibm.com/servers/eserver/serverproven/compat/us/>

Figure 2 shows the tape drive installed in the IBM DDS Tape Enablement Kit. This kit converts the tape drive to a 3.5 inch form factor for installation in supported servers (see Table 2). An example of such installation is shown in Figure 6.




Figure 2. DDS Generation 5 USB Tape Drive converted to 3.5 inch form factor (required for installation internally in supported System x servers)

External use

The DDS Generation 5 USB Tape Drive can be connected externally to specific servers as listed in Table 2. To do so requires the use of one of the following supported enclosures, and as listed in Table 4:

- IBM 1U Rackmount Tape Enclosure
- IBM 4U Rackmount Tape Enclosure (withdrawn)
- IBM Half High Tabletop Tape Enclosure

Note: Each of these enclosures also requires an IBM USB Enclosure Adapter Kit, 44E8869, to route the USB cabling from the tape drive to the rear of the enclosure. The IBM USB Enclosure Adapter Kit includes the following components:

- USB adapter/connector
- One 3 m (12 ft) USB cable
- One 25 cm (1 ft) USB cable

Table 4. External enclosures for use with the DDS Generation 5 USB Tape Drive

Description	Part number	Feature code
IBM 1U Rackmount Tape Enclosure	87651UX (AG)* 87651NX (AP and EMEA)†	8765HC1 fc 2290
IBM 4U Rackmount Tape Enclosure (withdrawn)	87664UX (AG)* 87664NX (AP and EMEA)†	Not available (product is withdrawn)
IBM Half High Tabletop Tape Enclosure	8767HHX (AG)* 87671NX (AP and EMEA)†	8767HC1 fc 2287
IBM USB Enclosure Adapter Kit‡	44E8869	5396

* These models are for customers in the Americas Group (AG - Canada, U.S., and countries in South America). These models ship with a NEMA 5-15P line cord.

† These models are for customers in the countries known collectively as Asia Pacific (AP) and Europe, Middle East, Africa (EMEA). These models do not ship with a line cord.

‡ See the above note.

For the latest information about supported enclosures and kits, see:

<http://ibm.com/servers/eserver/serverproven/compat/us/tape/39M5636.html>

Figure 3 shows the tape drive installed in the left bay of the IBM 1U Rackmount Tape Enclosure (87651UX).



Figure 3. DDS Generation 5 USB Tape Drive installed in the 1U Rackmount Tape Enclosure (left bay)

Figure 4 shows the tape drive installed with an open view of the the IBM 1U Rackmount Tape Enclosure (87651UX). The configuration uses the USB Enclosure Adapter Kit, 44E8869, to route an external USB connection to the tape drive inside the enclosure.



Figure 4. DDS Generation 5 USB Tape Drive installed with an open view of the 1U Rackmount Tape Enclosure

Figure 5 shows the tape drive installed in the IBM Half High Tabletop Tape Enclosure (8767HHX).



Figure 5. DDS Generation 5 USB Tape Drive installed in the Half High Tabletop Tape Enclosure

Popular configurations

This section illustrates how the DDS Generation 5 USB Tape Drive can be used in configurations.

Internal installation in an x3650 M3 server

Figure 6 shows the DDS Generation 5 USB Tape Drive installed internally in an x3650 M3 server. This configuration uses the Tape Enablement Kit option for x3650 M3, which allows customers to replace existing hot-swap disk drive bays with the USB tape drive. The enablement kit includes a bezel and assembly to convert the drive to a 3.5 inch tape drive.



Figure 6. The DDS Generation 5 USB Tape Drive installed internally in an x3650 M3 server

Table 5 lists the parts that are used.

Table 5. Components that are used when installing DDS Generation 5 USB Tape Drive into x3650 M3 server

Diagram reference	Part number/ machine type	Description	Quantity
1	7945	x3650 M3	1
2	59Y3806	Tape Enablement Kit option for x3650 M3	1
3	46C5399	DDS Generation 5 USB Tape Drive	1

Installation in a 1U external enclosure

Figure 7 shows the DDS Generation 5 USB Tape Drive installed in an IBM 1U Tape Drive External Enclosure and connected to a System x server.




Figure 7. The DDS Generation 5 USB Tape Drive installed in an IBM 1U Tape Drive External Enclosure and connected to x3650 M3 server

Table 6 lists the parts that are used.

Table 6. Components used when connecting DDS Generation 5 USB Tape Drive installed in external tape drive enclosure to x3650 M3 server

Diagram reference	Part number/ machine type	Description	Quantity
1	Varies	Supported System x server	1
2	44E8869	USB Enclosure Adapter Kit	1 per drive
3	46C5399	DDS Generation 5 USB Tape Drive	1
4	87651UX	IBM 1U Tape Drive External Enclosure	1

Figure 8 shows the USB cable connection to the back of the IBM 1U Tape Drive External Enclosure. The USB cable is part of the USB Enclosure Adapter Kit.



Figure 8. The DDS Generation 5 USB Tape Drive connection to the back of the external tape drive enclosure.

Supported software products

The DDS Generation 5 USB Tape Drive supports the following software products:

- CA Brighstor
- Tivoli Storage Manager
- Symantec Backup Exec
- Symantec Net Backup

Supported operating systems

The DDS Generation 5 USB Tape Drive supports the following operating systems:

- Microsoft Windows Server 2003 (x64)
- Microsoft Windows Server 2003 (x86)
- Microsoft Windows Server 2008 (x64)
- Microsoft Windows Server 2008 (x86)
- Microsoft Windows Server 2008 R2 (x64)
- Microsoft Windows Vista (x64)
- Microsoft Windows Vista (x86)
- Microsoft Windows XP (x64)
- Microsoft Windows XP (x86)
- Novell Open Enterprise Server
- Novell Open Enterprise Server 2
- Oracle Enterprise Linux 4 (x64)
- Oracle Enterprise Linux 4 (x86)
- Oracle Enterprise Linux 5 (x64)
- Oracle Enterprise Linux 5 (x86)
- Red Hat Enterprise Linux 4 (x64)
- Red Hat Enterprise Linux 4 (x86)
- Red Hat Enterprise Linux 5 (x64)
- Red Hat Enterprise Linux 5 (x86)
- Sun Solaris 10 (x64)
- Sun Solaris 10 (x86)
- SUSE Linux Enterprise Server 9 (x64)
- SUSE Linux Enterprise Server 9 (x86)
- SUSE Linux Enterprise Server 10 (x64)
- SUSE Linux Enterprise Server 10 (x86)
- SUSE Linux Enterprise Server 11 (x64)
- SUSE Linux Enterprise Server 11 (x86)

See IBM ServerProven for the latest information on the specific versions and service packs supported:

<http://ibm.com/servers/eserver/serverproven/compat/us/>. Select the blade server and then select the expansion card to see the supported operating systems.

Related publications

For more information, refer to the following resources:

- IBM US announcement letter for IBM DDS Generation 5 USB Tape Drive
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS109-591>
- IBM DDS Generation 5 USB Tape Drive overview
<http://www.ibm.com/systems/storage/tape/ddsgenx/index.html>
- IBM DDS Generation 5 USB Tape Drive specifications
<http://www.ibm.com/systems/storage/tape/ddsgenx/specifications.html>
- IBM DDS Generation 5 USB Tape Drive User's Guide
<http://www.ibm.com/support>
- Recommended tape drive media list - IBM System x
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-5074910>
- IBM Tape Storage Products Problem Determination and Service Guide
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-5079217>
- Installation Guide for IBM 1U Rackmount Tape Enclosure
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-64787>
- Installation Guide for IBM Half High Tabletop Tape Enclosure
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-64792>
- Installation Guide for DDS Tape Enablement Kit
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-5072866>
- System x tape software matrix
<http://www.ibm.com/support/docview.wss?uid=psg1TAPE-FILES>

Related product families

Product families related to this document are the following:

- [Backup Units](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2022. All rights reserved.

This document, TIPS0755, was created or updated on April 14, 2011.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.com/TIPS0755>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.com/TIPS0755>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

System x®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Windows Server®, Windows Vista®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.